

Series 200

Monitor

Features

- High accuracy
- Rapid T90 response
- Ergonomic design
- Simple operation
- Large easy to read display
- Remote sensor capability
- Portable & wall mountable
- Interchangeable sensor heads
- Battery & AC mains power



Specifications

Base unit

Measurement units	ppm
Removable / replaceable sensor head	Yes
On-board alarm *	Yes (dual alarm)
Alarm status display *	Yes
Alarm mute function *	Yes
Zero-cal function	Yes
Low battery indication	Yes
Sensor condition status	Yes
Stand-by mode	Yes
External signal for alarms & control	None
External signal functions	None
Analogue output	None
Power supply	12 VDC, 800 mA (factory supplied)
Rechargeable battery pack	9.6V (2100mA/hr Ni-MH)
Permanently fixable	Yes (screw fix or use R33 wall bracket)
Remote Sensor Capability	Yes (use R10 or R13 remote kit)
Enclosure rating	IP20 & NEMA 1 equivalent
Size (with sensor head)	195 x 122 x 54 (mm); 7 $\frac{7}{8}$ x 4 $\frac{3}{4}$ x 2 $\frac{1}{8}$ (in)
Weight (with sensor head and battery)	< 460 g; < 16 oz
Approvals	Part 15 of FCC Rules EN 50082-1: 1997 EN 50081-1: 1992



* Perchloroethylene sensors only